



# M3010

## LABELLING LINE FOR TWO SIDES APPLICATION

**Superior stabilizing counterroller** to ensure the product stability during the labelling.

**No motorized controller** for wraparound application.

**Stainless steel base** containing the electrical panel of the machine.

**New touch screen control box** that allows the setting of useful information for the correct application of labels



**Photocell** for opaque or micro for transparent labels.

It is possible **to install hot or dry overprinting units.**



# M3010

LABELLING LINE FOR TWO SIDES APPLICATIONS

## GENERAL FEATURES

Automatic labeller for applying two labels or more on cylindrical, flat and oval products at the same time. The machine consists in a conveyor and two of the following heads: Classic New 1, 2 or 3 and Plus. In case of wraparound label application a side conveyor is installed. It is also possible to install an hot or dry overprinting unit for marking alphanumerical variable data. The loading and unloading of products can done manually, or on a rotary table Ø 800 or 1000 mm, or alternatively directly from an existing production line.

## ACCESSORIES

Non motorized side wraparound conveyor - upper stabilizer conveyor lenght 500 or 900 - spacing wheel - orbital alignor - endless screw spacer - product stop device - 3 rolls centering system.

## TECHNICAL FEATURES

Product shape: flat; round; oval

Machine size

length mm 2000 width mm 1200 height mm 1500

Conveyor motor 0,57 Kw AC

	<b>Classic New 1</b>	<b>Classic New 2</b>	<b>Classic New 3</b>	<b>Plus</b>
Speed	20 mt/min	30 mt/min	40 mt/min	40 mt/min
Label reel size*				
Ø external max	mm 250	mm 250	mm 350	mm 350
Ø internal min	mm 40	mm 40	mm 40	mm 40
Power supply elettrica	230 V AC	230 V AC	230 V AC	230 V AC

## AVAILABLE MODELS

Classic New 1	Classic New 3
Classic New 2	Plus

\* Other sizes on request

