




Complete Lines Aeromatic PMA 600 - T6

Images






INTIMAC S.R.L.
Via XXV Aprile, 8
21054 Fagnano Olona (VA) - Italia
Tel. +39 0331 1693557
email: inti@intisrl.it



Product details

Category:	Complete Lines
Machine:	PMA 600 - T6
Machine code:	IT216

**Manufacturer:** Aeromatic**Year of construction:** n/a

Description

High speed mixer granulator: Aeromatic PMA 600

Gross volume: 600 Lt.

Normal working volume: 480 Lt.

Average granulated batch weight: 280 Kg

Impeller speeds: 86/172 rpm

Impeller motor capacities: 22/30 kW

Granulator speeds: 1500/3000 rpm

Granulator motor capacity: 7.5/11 kW

Fluidbed Dryer:

This is a steam-heated Fluidbed Dryer which is suit-able for processing batches between 100 and 300 kg depending on the characteristics of the product. The Dryer comprises a Stainless Steel Filter Housing with retractable Product Container.

The base of the container is fitted with a Stainless Steel wire-mesh.

Product to be processed is placed into the Product Container which is then positioned underneath the filter housing. The filled container is placed into the opening at the base of the column and pushed upwards by a pneumatic ram. It closes against a seal at the base of the column thus forming a closed system. Air is now drawn through this system by fan – ambient air is sucked in and through a Heating Register, through the perforated base of the product container and into the product which is dispersed and thoroughly dried within the Filter Housing.

A special Filter is fitted above the product contain-er inside the column and this prevents product particles to be sucked out of the column. During this process, the air supply is interrupted. An air exhaust duct is mounted At the end of the drying process, the product con-tainer is released and pulled out of the column for ease of disposal.

The operator controls are located in a separate console and include temperature controls and process timers.

Tecnica details:

Pressure shock resistance: 2 bar

Reacting pressure “ex” flap: 0.1 bar

“Ex” flat area 1.08 m²

Air preparation housing:

Pressure shock resistance 0.06 bar

Heating medium steam at 4 bar

Compress air connection 6 bar