



Water Treatment/Distillation Units/Reverse Osmosis/Pure Steam Generators GDN PSME 200 3E

Images



Product details

Category:	Sold
Machine:	PSME 200 3E
Machine code:	RS422
Manufacturer:	GDN
Year of construction:	2011



INTIMAC S.R.L.

Via XXV Aprile, 8
21054 Fagnano Olona (VA) - Italia
Tel. +39 0331 1693557
email: inti@intisrl.it

Description

Type PSME 200 3E - Electrical Multieffect Distiller

Year of construction: 2011

Material: Stainless steel

Internal finish: Mirror polished

External finish: Mirror polished

Connections: Welded

Dimensions:

Length 1400

Depth 1300

Height 3160

Bracket: Adjustable brackets

Voltage: 380 V AC \pm 4% , 50 Hz - three phase

Feed water type : PW water

Feed water flow rate: 220 lt/hr @ 20°C / 1-3 bar * Cooling water consumption: 227 lt/hr @ 20°C / 1-3 bar

Cooling water consumption: 227 lt/hr @ 15°-85°C* * Cooling water consumption: 227 lt/hr @ 15°-85°C

WFI production: 200 lt/h by gravity @ 85°-90°C* * Cooling water consumption: 227 lt/hr @ 15°-85°C

Electricity consumption: 55 Kw/hr

Compressed air pressure: 6-8 bar